Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
S145	1328	358/1.1.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2004/08/06 06:57
S146	1064	358/1.16.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2004/08/06 06:57
S147	475	715/501.1.ccls.	USPAT	OR	OFF	2004/08/06 06:58
S148	33	715/525.ccls.	USPAT	OR	OFF	2004/08/06 06:58
S157	15	((INTERCEPT$3 SAME PRINTER) SAME DATA) SAME SPOOL$3	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2004/08/05 15:52
S158	33	(INTERCEPT$3 SAME PRINT$3 SAME DOCUMENT) SAME COPY	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2004/08/05 16:08
S159	1411	358/1.1.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2004/08/06 07:02
S160	1194	358/1.16.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2004/08/06 07:04
S161	590	715/501.1.ccls.	USPAT	OR	OFF	2004/08/06 07:13
S162	56	715/525.ccls.	USPAT	OR	OFF	2004/08/06 06:59
S163	307	715/526.ccls.	USPAT	OR	OFF	2004/08/06 07:13
S164	63	715/527.ccls.	USPAT	OR	OFF	2004/08/06 07:14
S165	444	INTERCEPT$3 SAME SPOOL$3	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2004/08/06 08:19

S166	36	S165 same print$3	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2004/08/06 08:05
S167	4	S165 same (modify$3 alter$3)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2004/08/06 08:22
S168	2	S165 same (redirect$3)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2004/08/06 08:34
S169	2	second spooler intercept$3	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	SAME	ON	2004/08/06 08:38
S170	0	spoolers intercept$3	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	WITH	OFF	2004/08/06 08:38

PORTAL
US Patent & Trademark Office

Subscribe (Full Service) Register (Limited Service, Free) Login

Search: The ACM Digital Library The Guide

INTERCEPT???<p> PRINTER <p> DATA<p> SPOOL???

SEARCH

THE ACM DIGITAL LIBRARY

Feedback Report a problem Satisfaction survey

Terms used **INTERCEPT??? p PRINTER p DATA p SPOOL???**

Found **104** of **140,980**

Sort results by: relevance

Display results: expanded form

Save results to a Binder

Search Tips

Open results in a new window

Try an Advanced Search

Try this search in The ACM Guide

Results 1 - 20 of 104

Result page: **1** 2 3 4 5 6 next

Relevance scale

1 Session 7: Locality-sensitive hashing scheme based on p-stable distributions

Mayur Datar, Nicole Immorlica, Piotr Indyk, Vahab S. Mirrokni

June 2004 **Proceedings of the twentieth annual symposium on Computational geometry**

Full text available: pdf(210.60 KB) Additional Information: full citation, abstract, references, index terms

We present a novel Locality-Sensitive Hashing scheme for the Approximate Nearest Neighbor Problem under l_p norm, based on p-stable distributions.Our scheme improves the running time of the earlier algorithm for the case of the l_p norm. It also yields the first known provably efficient approximate NN algorithm for the case $p<1$. We also show that the algorithm finds the exact near neigbhor in $O(\log n)$ time for data satisfying certa ...

Keywords: p-stable distributions, approximate nearest neighbor, locally sensitive hashing, sublinear algorithm

2 P-TAC: a parallel intermediate language

Zena Ariola, Arvind

November 1990 **Proceedings of the fourth international conference on Functional programming languages and computer architecture**

Full text available: pdf(1.47 MB) Additional Information: full citation, references, citings, index terms

3 Factorization of differential systems in characteristic p

Thomas Cluzeau

August 2003 **Proceedings of the 2003 international symposium on Symbolic and algebraic computation**

Full text available: pdf(220.32 KB) Additional Information: full citation, abstract, references, citings, index terms

We present an algorithm for factoring differential systems with coefficients in $\mathbf{F}p(z)$. Such an algorithm has already been given by van der Put in [20], [24, 13.1] and [22]. We recast his ideas to handle systems directly and we add some comparisons of strategies, an implementation in Maple[1] and a complexity analysis. The central tool for factoring in characteristic p is the p curvature. We prove the links between the p-curvature and ...

Keywords: characteristic p, differential systems, eigenring, factorization, p-curvature

4 A technique for solving ordinary differential equations using Riemann's P-functions

Shunro Watanabe
August 1981 **Proceedings of the fourth ACM symposium on Symbolic and algebraic computation**

Full text available: pdf(476.39 KB) Additional Information: full citation, abstract, references, index terms

This paper presents an algorithmic approach to symbolic solution of 2nd order linear ODEs. The algorithm consists of two parts. The first part involves complete algorithms for hypergeometric equations and hypergeometric equations of confluent type. These algorithms are based on Riemann's P-functions and Hukuhara's P-functions respectively. Another part involves an algorithm for transforming a given equation to a hypergeometric equation or a hypergeometric equation of confluent type. The tra ...

5 Algebraic algorithms using p-adic constructions

David Y. Y. Yun
August 1976 **Proceedings of the third ACM symposium on Symbolic and algebraic computation**

Full text available: pdf(1.05 MB) Additional Information: full citation, abstract, references, index terms

Machine computation of many algebraic operations of interest and utility to mathematicians and scientists has received increasing attention in the recent years. A variety of terminology has been used to describe this area of mathematical computation. Among these are symbolic manipulation, computer algebra, algebraic methods, constructive algebra, and seminumerical algorithms. Whatever name is chosen for the field currently known as symbolic and algebraic manipulation, the most fundamental p ...

6 Sparse sets in NP-P: Exptime versus nexptime

J. Hartmanis, V. Sewelson, N. Immerman
December 1983 **Proceedings of the fifteenth annual ACM symposium on Theory of computing**

Full text available: pdf(774.35 KB) Additional Information: full citation, abstract, references, citings, index terms

This paper investigates the structural properties of sets in NP-P and shows that the computational difficulty of lower density sets in NP depends explicitly on the relations between higher deterministic and nondeterministic time-bounded complexity classes. The paper exploits the recently discovered upward separation method, which shows for example that there exist sparse sets in NP-Pif and only if EXPTIME @@@@ NEXPT ...

7 Parallel algorithms for unification and other complete problems in p

Jeffrey Scott Vitter, Roger A. Simons
January 1984 **Proceedings of the 1984 annual conference of the ACM on The fifth generation challenge**

Full text available: pdf(916.57 KB) Additional Information: full citation, abstract, references, citings, index terms

Unification is a basic operation in theorem proving, in type inference algorithms, and in logic programming languages such as Prolog. Prolog will play a major role in software development for the Fifth Generation project, and thus developing fast algorithms for unification is an important goal. This paper shows that the running time for a linear unification algorithm can often be improved substantially by use of parallel processing. The same is true for algorithms for some other complete pr ...

8 Synthesis of p-valued asynchronous sequential circuits by using a general clock function

J. L. Huertas, J. I. Acha
May 1976 **Proceedings of the sixth international symposium on Multiple-valued logic**

Full text available: pdf(338.06 KB) Additional Information: full citation, abstract, references, index terms

A selfsynchronization method for implementing p-v&abarbelow;lued asynchronous sequential machines is given. The general clock function of each multistable type is

devel&obarbelow;ped. This function is the kernel of the proposed adapt&ibarbelow;ve synchronism. An implementation of this function is given which does not depend on the number of logic levels. Constraints and advantages are discussed.

9 Direct implementation of compiler specifications or the pascal p-code compiler revisited

Don Milos, Uwe Pleban, George Loegel

January 1984 **Proceedings of the 11th ACM SIGACT-SIGPLAN symposium on Principles of programming languages**

Full text available: pdf(661.16 KB) Additional Information: full citation, abstract, references, citings, index terms

We have developed a complete formal specification of the translation semantics of the Pascal P-compiler. The specification is written as a semantic grammar (a variant of extended attribute grammars), and has been extensively tested and debugged with the aid of Lawrence Paulson's experimental semantics processor. The translation semantics models the operational aspects of compilation in detail. It is one-pass, embodying static semantic checking, address assignment, code generation, and a cer ...

10 Session 5B: Server scheduling in the L_p norm: a rising tide lifts all boat

Nikhil Bansal, Kirk Pruhs

June 2003 **Proceedings of the thirty-fifth annual ACM symposium on Theory of computing**

Full text available: pdf(249.70 KB) Additional Information: full citation, abstract, references, index terms

Often server systems do not implement the best known algorithms for optimizing average Quality of Service (QoS) out of concern of that these algorithms may be insufficiently fair to individual jobs. The standard method for balancing average QoS and fairness is optimize the L_p metric, $1 < p < \infty$. Thus we consider server scheduling strategies to optimize the L_p norms of the standard QoS measures, flow and stretch. We first show that there is ...

Keywords: flow time, multilevel feedback, resource augmentation, scheduling, shortest elapsed time first, shortest job first, shortest remaining processing time

11 P-uniform circuit complexity

Eric W. Allender

October 1989 **Journal of the ACM (JACM)**, Volume 36 Issue 4

Full text available: pdf(1.49 MB) Additional Information: full citation, abstract, references, citings, index terms

Much complexity-theoretic work on parallelism has focused on the class NC, which is defined in terms of logspace-uniform circuits. Yet P-uniform circuit complexity is in some ways a more natural setting for studying feasible parallelism. In this paper, P-uniform NC (PUNC) is characterized in terms of space-bounded AuxPDAs and alternating Turing Machines with bounded access to the input. The notions of general-purpose and special-purpose computation are considered, and a general-purpose para ...

12 Matrix rounding under the *Lp*-discrepancy measure and its application to digital halftoning

Tetsuo Asano, Naoki Katoh, Koji Obokata, Takeshi Tokuyama

January 2002 **Proceedings of the thirteenth annual ACM-SIAM symposium on Discrete algorithms**

Full text available: pdf(1.03 MB) Additional Information: full citation, abstract, references, citings

In this paper we study the problem of rounding a real-valued matrix into an integer-valued matrix to minimize an *Lp*-discrepancy measure between them. To define the *Lp*-discrepancy measure, we introduce a family *F* of regions (rigid submatrices) of the matrix, and consider a hypergraph defined by the family. The difficulty of the problem depends on the choice of the region family *F*. We first investigate the rounding problem by using integer

programm ...

13 Database and digital library technologies: The P-tree algebra
Qin Ding, Maleq Khan, Amalendu Roy, William Perrizo
March 2002 **Proceedings of the 2002 ACM symposium on Applied computing**

Full text available: pdf(469.32 KB) Additional Information: full citation, abstract, references, citings, index terms

The Peano Count Tree (P-tree) is a quadrant-based lossless tree representation of the original spatial data. The idea of P-tree is to recursively divide the entire spatial data, such as Remotely Sensed Imagery data, into quadrants and record the count of 1-bits for each quadrant, thus forming a quadrant count tree. Using P-tree structure, all the count information can be calculated quickly. This facilitates efficient ways for data mining. In this paper, we will focus on the algebra and propertie ...

Keywords: Peano ordering, compression, quadrant, spatial data, tree structure

14 P-MIP: paging extensions for mobile IP
Xiaowei Zhang, Javier Gomez Castellanos, Andrew T. Campbell
April 2002 **Mobile Networks and Applications**, Volume 7 Issue 2

Full text available: pdf(272.68 KB) Additional Information: full citation, abstract, references, index terms

As the number of Mobile IP users grows, so will the signalling overhead associated with Internet mobility management in the core IP network. This presents a significant challenge to Mobile IP as the number of mobile devices scale-up. In cellular networks, registration and paging techniques are used to minimize the signalling overhead and optimize the mobility management performance. Currently, Mobile IP supports registration but not paging. In this paper, we argue that Mobile IP should be extend ...

Keywords: Mobile IP, mobility management, paging

15 Optimal P/N width ratio selection for standard cell libraries
David S. Kung, Ruchir Puri
November 1999 **Proceedings of the 1999 IEEE/ACM international conference on Computer-aided design**

Full text available: pdf(195.26 KB) Additional Information: full citation, abstract, references, citings, index terms

The effectiveness of logic synthesis to satisfy increasingly tight timing constraints in deep-submicron high-performance circuits heavily depends on the range and variety of logic gates available in the standard cell library. Primarily, research in the design of high-performance standard cell libraries has been focused on drive strength selection of various logic gates. Since CMOS logic circuit delays not only depend on the drive strength of each gate but also on its P/N width ratio, it is ...

16 Ancient and new algorithms for load balancing in the Lp norm
Adi Avidor, Yossi Azar, Jiří Sgall
January 1998 **Proceedings of the ninth annual ACM-SIAM symposium on Discrete algorithms**

Full text available: pdf(1.03 MB) Additional Information: full citation, references, index terms

17 A new way to use semidefinite programming with applications to linear equations mod p
Gunnar Andersson, Lars Engebretsen, Johan Håstad
January 1999 **Proceedings of the tenth annual ACM-SIAM symposium on Discrete**

algorithms

Full text available: pdf(1.03 MB) Additional Information: full citation, references, citings, index terms

18 The P-range tree: a new data structure for range searching in secondary memory

Sairam Subramanian, Sridhar Ramaswamy

January 1995 **Proceedings of the sixth annual ACM-SIAM symposium on Discrete algorithms**

Full text available: pdf(1.22 MB) Additional Information: full citation, references, citings, index terms

19 The robustness of the p-norm algorithms

Claudio Gentile, Nick Littlestone

July 1999 **Proceedings of the twelfth annual conference on Computational learning theory**

Full text available: pdf(1.30 MB) Additional Information: full citation, references, citings, index terms

20 Classifying proteins by family using the product of correlated p-values

Timothy L. Bailey, William Noble Grundy

April 1999 **Proceedings of the third annual international conference on Computational molecular biology**

Full text available: pdf(628.21 KB) Additional Information: full citation, references, index terms

Results 1 - 20 of 104 Result page: **1** 2 3 4 5 6 next

The ACM Portal is published by the Association for Computing Machinery. Copyright © 2004 ACM, Inc.

Terms of Usage Privacy Policy Code of Ethics Contact Us

Useful downloads: Adobe Acrobat QuickTime Windows Media Player Real Player

PORTAL
US Patent & Trademark Office

Subscribe (Full Service) Register (Limited Service, Free) Login

Search: The ACM Digital Library The Guide

INTERCEPT???<p> PRINTER <p> DATA<p> SPOOL???

SEARCH

THE ACM DIGITAL LIBRARY

Feedback Report a problem Satisfaction survey

Terms used **INTERCEPT??? p PRINTER p DATA p SPOOL???**

Found **104** of **140,980**

Sort results by: relevance

Display results: expanded form

Save results to a Binder

Search Tips

Open results in a new window

Try an Advanced Search

Try this search in The ACM Guide

Results 1 - 20 of 104

Result page: **1** 2 3 4 5 6 next

Relevance scale

1 Session 7: Locality-sensitive hashing scheme based on p-stable distributions

Mayur Datar, Nicole Immorlica, Piotr Indyk, Vahab S. Mirrokni

June 2004 **Proceedings of the twentieth annual symposium on Computational geometry**

Full text available: pdf(210.60 KB) Additional Information: full citation, abstract, references, index terms

We present a novel Locality-Sensitive Hashing scheme for the Approximate Nearest Neighbor Problem under l_p norm, based on p-stable distributions.Our scheme improves the running time of the earlier algorithm for the case of the l_p norm. It also yields the first known provably efficient approximate NN algorithm for the case $p<1$. We also show that the algorithm finds the exact near neigbhor in $O(\log n)$ time for data satisfying certa ...

Keywords: p-stable distributions, approximate nearest neighbor, locally sensitive hashing, sublinear algorithm

2 P-TAC: a parallel intermediate language

Zena Ariola, Arvind

November 1990 **Proceedings of the fourth international conference on Functional programming languages and computer architecture**

Full text available: pdf(1.47 MB) Additional Information: full citation, references, citings, index terms

3 Factorization of differential systems in characteristic p

Thomas Cluzeau

August 2003 **Proceedings of the 2003 international symposium on Symbolic and algebraic computation**

Full text available: pdf(220.32 KB) Additional Information: full citation, abstract, references, citings, index terms

We present an algorithm for factoring differential systems with coefficients in $\mathbf{F}p(z)$. Such an algorithm has already been given by van der Put in [20], [24, 13.1] and [22]. We recast his ideas to handle systems directly and we add some comparisons of strategies, an implementation in Maple[1] and a complexity analysis. The central tool for factoring in characteristic p is the p curvature. We prove the links between the p-curvature and ...

Keywords: characteristic p, differential systems, eigenring, factorization, p-curvature

4 A technique for solving ordinary differential equations using Riemann's P-functions

Shunro Watanabe
August 1981 **Proceedings of the fourth ACM symposium on Symbolic and algebraic computation**

Full text available: pdf(476.39 KB) Additional Information: full citation, abstract, references, index terms

This paper presents an algorithmic approach to symbolic solution of 2nd order linear ODEs. The algorithm consists of two parts. The first part involves complete algorithms for hypergeometric equations and hypergeometric equations of confluent type. These algorithms are based on Riemann's P-functions and Hukuhara's P-functions respectively. Another part involves an algorithm for transforming a given equation to a hypergeometric equation or a hypergeometric equation of confluent type. The tra ...

5 Algebraic algorithms using p-adic constructions

David Y. Y. Yun
August 1976 **Proceedings of the third ACM symposium on Symbolic and algebraic computation**

Full text available: pdf(1.05 MB) Additional Information: full citation, abstract, references, index terms

Machine computation of many algebraic operations of interest and utility to mathematicians and scientists has received increasing attention in the recent years. A variety of terminology has been used to describe this area of mathematical computation. Among these are symbolic manipulation, computer algebra, algebraic methods, constructive algebra, and seminumerical algorithms. Whatever name is chosen for the field currently known as symbolic and algebraic manipulation, the most fundamental p ...

6 Sparse sets in NP-P: Exptime versus nexptime

J. Hartmanis, V. Sewelson, N. Immerman
December 1983 **Proceedings of the fifteenth annual ACM symposium on Theory of computing**

Full text available: pdf(774.35 KB) Additional Information: full citation, abstract, references, citings, index terms

This paper investigates the structural properties of sets in NP-P and shows that the computational difficulty of lower density sets in NP depends explicitly on the relations between higher deterministic and nondeterministic time-bounded complexity classes. The paper exploits the recently discovered upward separation method, which shows for example that there exist sparse sets in NP-Pif and only if EXPTIME @@@@ NEXPT ...

7 Parallel algorithms for unification and other complete problems in p

Jeffrey Scott Vitter, Roger A. Simons
January 1984 **Proceedings of the 1984 annual conference of the ACM on The fifth generation challenge**

Full text available: pdf(916.57 KB) Additional Information: full citation, abstract, references, citings, index terms

Unification is a basic operation in theorem proving, in type inference algorithms, and in logic programming languages such as Prolog. Prolog will play a major role in software development for the Fifth Generation project, and thus developing fast algorithms for unification is an important goal. This paper shows that the running time for a linear unification algorithm can often be improved substantially by use of parallel processing. The same is true for algorithms for some other complete pr ...

8 Synthesis of p-valued asynchronous sequential circuits by using a general clock function

J. L. Huertas, J. I. Acha
May 1976 **Proceedings of the sixth international symposium on Multiple-valued logic**

Full text available: pdf(338.06 KB) Additional Information: full citation, abstract, references, index terms

A selfsynchronization method for implementing p-v&abarbelow;lued asynchronous sequential machines is given. The general clock function of each multistable type is

devel&obarbelow;ped. This function is the kernel of the proposed adapt&ibarbelow;ve synchronism. An implementation of this function is given which does not depend on the number of logic levels. Constraints and advantages are discussed.

9 Direct implementation of compiler specifications or the pascal p-code compiler revisited

Don Milos, Uwe Pleban, George Loegel
January 1984 **Proceedings of the 11th ACM SIGACT-SIGPLAN symposium on Principles of programming languages**

Full text available: pdf(661.16 KB) Additional Information: full citation, abstract, references, citings, index terms

We have developed a complete formal specification of the translation semantics of the Pascal P-compiler. The specification is written as a semantic grammar (a variant of extended attribute grammars), and has been extensively tested and debugged with the aid of Lawrence Paulson's experimental semantics processor. The translation semantics models the operational aspects of compilation in detail. It is one-pass, embodying static semantic checking, address assignment, code generation, and a cer ...

10 Session 5B: Server scheduling in the L_p norm: a rising tide lifts all boat

Nikhil Bansal, Kirk Pruhs
June 2003 **Proceedings of the thirty-fifth annual ACM symposium on Theory of computing**

Full text available: pdf(249.70 KB) Additional Information: full citation, abstract, references, index terms

Often server systems do not implement the best known algorithms for optimizing average Quality of Service (QoS) out of concern of that these algorithms may be insufficiently fair to individual jobs. The standard method for balancing average QoS and fairness is optimize the L_p metric, $1 < p < \infty$. Thus we consider server scheduling strategies to optimize the L_p norms of the standard QoS measures, flow and stretch. We first show that there is ...

Keywords: flow time, multilevel feedback, resource augmentation, scheduling, shortest elapsed time first, shortest job first, shortest remaining processing time

11 P-uniform circuit complexity

Eric W. Allender
October 1989 **Journal of the ACM (JACM)**, Volume 36 Issue 4

Full text available: pdf(1.49 MB) Additional Information: full citation, abstract, references, citings, index terms

Much complexity-theoretic work on parallelism has focused on the class NC, which is defined in terms of logspace-uniform circuits. Yet P-uniform circuit complexity is in some ways a more natural setting for studying feasible parallelism. In this paper, P-uniform NC (PUNC) is characterized in terms of space-bounded AuxPDAs and alternating Turing Machines with bounded access to the input. The notions of general-purpose and special-purpose computation are considered, and a general-purpose para ...

12 Matrix rounding under the *Lp*-discrepancy measure and its application to digital halftoning

Tetsuo Asano, Naoki Katoh, Koji Obokata, Takeshi Tokuyama
January 2002 **Proceedings of the thirteenth annual ACM-SIAM symposium on Discrete algorithms**

Full text available: pdf(1.03 MB) Additional Information: full citation, abstract, references, citings

In this paper we study the problem of rounding a real-valued matrix into an integer-valued matrix to minimize an *Lp*-discrepancy measure between them. To define the *Lp*-discrepancy measure, we introduce a family *F* of regions (rigid submatrices) of the matrix, and consider a hypergraph defined by the family. The difficulty of the problem depends on the choice of the region family *F*. We first investigate the rounding problem by using integer

programm ...

13 Database and digital library technologies: The P-tree algebra
Qin Ding, Maleq Khan, Amalendu Roy, William Perrizo
March 2002 **Proceedings of the 2002 ACM symposium on Applied computing**

Full text available: pdf(469.32 KB) Additional Information: full citation, abstract, references, citings, index terms

The Peano Count Tree (P-tree) is a quadrant-based lossless tree representation of the original spatial data. The idea of P-tree is to recursively divide the entire spatial data, such as Remotely Sensed Imagery data, into quadrants and record the count of 1-bits for each quadrant, thus forming a quadrant count tree. Using P-tree structure, all the count information can be calculated quickly. This facilitates efficient ways for data mining. In this paper, we will focus on the algebra and propertie ...

Keywords: Peano ordering, compression, quadrant, spatial data, tree structure

14 P-MIP: paging extensions for mobile IP
Xiaowei Zhang, Javier Gomez Castellanos, Andrew T. Campbell
April 2002 **Mobile Networks and Applications**, Volume 7 Issue 2

Full text available: pdf(272.68 KB) Additional Information: full citation, abstract, references, index terms

As the number of Mobile IP users grows, so will the signalling overhead associated with Internet mobility management in the core IP network. This presents a significant challenge to Mobile IP as the number of mobile devices scale-up. In cellular networks, registration and paging techniques are used to minimize the signalling overhead and optimize the mobility management performance. Currently, Mobile IP supports registration but not paging. In this paper, we argue that Mobile IP should be extend ...

Keywords: Mobile IP, mobility management, paging

15 Optimal P/N width ratio selection for standard cell libraries
David S. Kung, Ruchir Puri
November 1999 **Proceedings of the 1999 IEEE/ACM international conference on Computer-aided design**

Full text available: pdf(195.26 KB) Additional Information: full citation, abstract, references, citings, index terms

The effectiveness of logic synthesis to satisfy increasingly tight timing constraints in deep-submicron high-performance circuits heavily depends on the range and variety of logic gates available in the standard cell library. Primarily, research in the design of high-performance standard cell libraries has been focused on drive strength selection of various logic gates. Since CMOS logic circuit delays not only depend on the drive strength of each gate but also on its P/N width ratio, it is ...

16 Ancient and new algorithms for load balancing in the Lp norm
Adi Avidor, Yossi Azar, Jiří Sgall
January 1998 **Proceedings of the ninth annual ACM-SIAM symposium on Discrete algorithms**

Full text available: pdf(1.03 MB) Additional Information: full citation, references, index terms

17 A new way to use semidefinite programming with applications to linear equations mod p
Gunnar Andersson, Lars Engebretsen, Johan Håstad
January 1999 **Proceedings of the tenth annual ACM-SIAM symposium on Discrete**

algorithms

Full text available: pdf(1.03 MB) Additional Information: full citation, references, citings, index terms

18 The P-range tree: a new data structure for range searching in secondary memory

Sairam Subramanian, Sridhar Ramaswamy

January 1995 **Proceedings of the sixth annual ACM-SIAM symposium on Discrete algorithms**

Full text available: pdf(1.22 MB) Additional Information: full citation, references, citings, index terms

19 The robustness of the p-norm algorithms

Claudio Gentile, Nick Littlestone

July 1999 **Proceedings of the twelfth annual conference on Computational learning theory**

Full text available: pdf(1.30 MB) Additional Information: full citation, references, citings, index terms

20 Classifying proteins by family using the product of correlated p-values

Timothy L. Bailey, William Noble Grundy

April 1999 **Proceedings of the third annual international conference on Computational molecular biology**

Full text available: pdf(628.21 KB) Additional Information: full citation, references, index terms

Results 1 - 20 of 104 Result page: **1** 2 3 4 5 6 next

The ACM Portal is published by the Association for Computing Machinery. Copyright © 2004 ACM, Inc.
Terms of Usage Privacy Policy Code of Ethics Contact Us

Useful downloads: Adobe Acrobat QuickTime Windows Media Player Real Player

Your search matched **0** of **1058483** documents.
A maximum of **500** results are displayed, **15** to a page, sorted by **Relevance** **Descending** order.

Refine This Search:
You may refine your search by editing the current search expression or enteri new one in the text box.

intercept??? <paragraph> printer <paragraph> data < Search

☐ Check to search within this result set

Results Key:
JNL = Journal or Magazine **CNF** = Conference **STD** = Standard

Results:
No documents matched your query.

Copyright © 2004 IEEE — All rights reserved